



Norm	Werkstoff	Querschnitt		Störkonturen		Gleiteinsatz erhältlich	Klemmhebel als Zubehör erhältlich	
		AL	NI	$d_1$	s			k Klemmlänge
GN 131.1 GN 131.2 Seite 1954	x	x	18	-	25	-	ja	ja
GN 132.1 GN 132.2 Seite 1955	x	-	30 40 50 60	-	40 56 65 80	-	ja	ja
GN 132.15 GN 132.25 Seite 1956	-	x	30 50	-	40 65	-	ja	ja
GN 133.1 GN 133.2 Seite 1957	x	-	18 30 50	-	40 65	-	ja	ja
GN 134.1 GN 134.2 GN 135.1 Seite 1978	x	-	30 40 50	30 40 50	50 60 76	-	nein	ja
GN 145.1 Seite 1958	x	-	18	-	25	35	ja	ja
GN 146.1 GN 146.13 Seite 1959	x	-	30 40 50 60	-	40 56 65 80	52 78 92 110	ja	ja
GN 146.15 GN 146.16 Seite 1961	-	x	30 50	-	40 65	52 92	ja	ja
GN 147.1 Seite 1980	x	-	-	30 40 50	50 76	50 76	nein	ja

Norm	Werkstoff	Werkstoff		Querschnitt		Störkonturen		Gleiteinsatz erhältlich	Klemmhebel als Zubehör erhältlich
		AL	NI	d <sub>1</sub>	s	k Klemmlänge	x Flansch		
<b>GN 162.1</b> Seite 1963		-	x	18	-	40	-	ja	ja
<b>GN 163.1</b> Seite 1964		x	-	30 40 50 60	-	50 70 85 100	-	ja	nein
<b>GN 163.15</b> Seite 1965		-	x	30 50	-	50 85	-	ja	ja
<b>GN 165.1</b> Seite 1981		x	-	-	30 40 50	58 91	-	nein	ja
<b>GN 273.1</b> Seite 1969		x	-	18	-	25	-	ja	ja
<b>GN 274.1</b> Seite 1970		x	-	30 40 50	-	40 65	-	ja	ja
<b>GN 277.1</b> Seite 1971		x	-	18	-	25	-	ja	ja
<b>GN 278.1</b> Seite 1972		x	-	30 40 50	-	40 65	-	ja	ja
<b>GN 191.1</b> Seite 1966		x	x	18	-	25	-	ja	ja
<b>GN 192.1</b> Seite 1967		x	-	30 40 50 60	-	40 56 65 80	-	ja	ja
<b>GN 192.15</b> Seite 1968		-	x	30 50	-	37 65	-	ja	ja